



DIMENSIONS; (ALL ARE IN INCHES)

ELL SIZE (CORE/JACKET)	B		C		D		E		F		COUPLING SIZE	NO. OF BOLTS 150#	DIA. OF BOLTS 150#	DIA. OF BOLTS 300#	
	150#	300#	150#	300#	150#	300#	150#	300#	150#	300#					
1 X 2	5	3/4	7/8	6	6 1/2	4 1/2	5	3 3/8	1 1/4	7/8	1/2	4	8	3/4	3/4
2 X 3	7	15/16	1 1/8	7 1/2	8 1/4	6	6 5/8	5	2 7/16	1 1/4	3/4	4	8	3/4	7/8
3 X 4	8	15/16	1 1/4	9	10	7 1/2	7 7/8	6 3/16	2 1/16	1 3/4	3/4	8	8	3/4	7/8
4 X 6	10	1 1/16	1 1/2	11	12 1/2	9 1/2	10 7/8	8 1/2	3 1/2	2 5/16	3/4	8	12	7/8	7/8
6 X 8	12	1 1/8	1 3/8	13 1/2	15	11 3/4	13	10 3/8	4 1/8	2 7/8	3/4	8	12	7/8	1
8 X 10	14	1 3/16	1 7/8	16	17 1/2	14 1/4	15 1/4	12 3/4	4 3/16	3 3/8	1	12	16	1	1 1/8
10 X 12	16	1 1/4	2	19	20 1/2	17	17 3/4	15	5 1/4	3 3/4	1	12	16	1	1 1/4

DATE	SYM	REVISION RECORD	BY
	○		

TOLERANCES  
 (EXCEPT AS NOTED)  
 DECIMAL  
 .X = ±.015  
 .XX = ±.010  
 .XXX = ±.005  
 FRACTIONAL  
 ± 1/64

TITLE  
 SIZE AND DIMENSIONS/FABRICATED  
 JACKETED 45° ELL

Flextrol, Inc.  
 192 Browns Hill Road  
 Locust, NC 28097

DRAWN BY ALP  
 DATE 7/18/08  
 TAG NO: X

ANGLE  
 ± 30'