



DIMENSIONS (ALL ARE IN INCHES)

CROSS SIZE (CORE/JACKET)	A	B		C		D		E	F		COUPLING SIZE	NO. OF BOLT HOLES		DIA. OF BOLT HOLES	
		150#	300#	150#	300#	150#	300#		150#	300#		150#	300#	150#	300#
1 X 2	5	3/4	7/8	6	6 1/2	4 3/4	5	5 5/8	1 1/4	7/8	1/2	4	8	3/4	3/4
2 X 3	7	15/16	1 1/8	7 1/2	8 1/4	6	6 5/8	5	2 5/16	1 3/4	3/4	4	8	3/4	7/8
3 X 4	8	15/16	1 1/4	9	10	7 1/2	7 7/8	6 3/16	2 9/16	1 3/4	3/4	8	8	3/4	7/8
4 X 6	10	1	1 1/16	11	12 1/2	9 1/2	10 5/8	8 1/2	3 1/2	2 5/16	3/4	8	12	7/8	7/8
6 X 8	12	1 1/8	1 5/8	13 1/2	15	11 3/4	13	10 5/8	4 1/8	2 7/8	3/4	8	12	7/8	1
8 X 10	15	1 3/16	1 7/8	16	17 1/2	14 1/4	15 1/4	12 3/4	4 13/16	3 3/8	1	12	16	1	1 1/8
10 X 12	18	1 1/4	2	19	20 1/2	17	17 3/4	15	5 1/4	3 3/4	1	12	16	1	1 1/4

TOLERANCES (EXCEPT AS NOTED)	Flextrol Corp. 192 Browns Hill Road Locust, NC 28097	
DECIMAL .X= ±.015 .XX= ±.010 .XXX= ±.005	TITLE SIZE AND DIMENSIONS/FABRICATED JACKETED 45° ELL	
FRACTIONAL ±1/64		
ANGULAR ±30'	DRAWN BY ALP DATE 6/21/13	CAPPED JACKETED 45° ELL

DATE	○	REVISION RECORD	BY
------	---	-----------------	----